

Single Phase Off-Grid Inverter

SUN-3.6/5/6K-OG01LP1-EU-AM2



Colorful touch LCD, IP65 protection degree

16

Max. 16 pcs parallel for off-grid operation;
Support multiple batteries parallel

135

Max. charging/discharging current of 135A



Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model	SUN-3.6K-OG01LP1-EU-AM2		SUN-5K-OG01LP1-EU-AM2	SUN-6K-OG01LP1-EU-AM2
Battery Input Data				
Battery Type	Lead-acid or Lithium-ion			
Battery Voltage Range (V)	40-60			
Max. Charging Current (A)	90	120	135	
Max. Discharging Current (A)	90	120	135	
Charging Strategy for Li-ion Battery	Self-adaption to BMS			
Number of Battery Input	1			
PV String Input Data				
Max. PV Access Power (W)	7200	10000	12000	
Max. PV Input Power (W)	5760	8000	9600	
Max. PV Input Voltage (V)	500			
Start-up Voltage (V)	125			
MPPT Voltage Range (V)	150-425			
Rated PV Input Voltage (V)	370			
Max. Operating PV Input Current (A)	18+18			
Max. Input Short-Circuit Current (A)	27+27			
No. of MPP Trackers/ No. of Strings MPP Tracker	2/1+1			
AC Output Data				
Rated AC Output Power (VA/W)	3600	5000	6000	
Max. AC Output Power (VA/W)	3600	5000	6000	
Max. AC Output Current (A)	15.7	21.8	26.1	
Peak Power (W)	2 times of rated power, 10s			
Rated Output Voltage (V)	230			
Output Type	L+N+PE			
Rated Output Frequency (Hz)	50/60			
Output Voltage Waveform	Pure Sine Wave			
Total Current Harmonic Distortion THDi	<3%			
AC Input Data (Grid and Generator)				
Max. Input Power to Battery (W)	3600	5000	6000	
Rated Input Voltage/Range (V)	230/90-280			
Rated Input Frequency (Hz)	50/60			
Grid Input Current (A)	35			
Generator Input Current (A)	35			
Efficiency				
Max. Efficiency	97.6%			
Euro Efficiency	96.5%			
MPPT Efficiency	>99%			
Equipment Protection				
Integrated	DC Polarity Reverse Connection Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Overvoltage Load Drop Protection, Ground Fault Current Monitoring, Arc fault circuit interrupter (AFCI), Power Network Monitoring, Earth Fault Detection, DC Input Switch, Surge protection level, DC Terminal Insulation Impedance Monitoring			
Surge Protection Level	TYPE II(DC), TYPE II(AC)			
Interface				
Communication Interface	RS485/RS232/CAN			
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)			
General Data				
Operating Temperature Range ()	-40 to +60°C, >45°C Derating			
Permissible Ambient Humidity	0-100%			
Permissible Altitude	3000m			
Noise (dB)	<45			
Ingress Protection(IP) Rating	IP 65			
Inverter Topology	Non-Isolated			
Over Voltage Category	OVC II(DC), OVC III(AC)			
Cabinet Size (WxHxD mm)	306×427.5×175.77 (Excluding Connectors and Brackets)			
Weight (kg)	12.5			
Type of Cooling	Intelligent Air Cooling			
Warranty	5 Years/10 Years the Warranty Period Depends the Final Installation Site of Inverter, More Info Please Refer to Warranty Policy			
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			