

## FLOOR STAND TYPE LIFEPO4 BATTERY

51.2VDC SERIES 460Ah



## **FEATURES**

- ♦ Built-in intelligent BMS
- ♦ ≥ 8000+ cycle life
- ♦ A+ grade brand battery cell

- Comply with ROSH standards
- Design life up to 10 years at 25°
- No active cooling system is required

## **APPLICATION**

- Oil and electricity hybrid energy storage system.
- Grid frequency adjustment energy storage system.
- New energy communication base station, Core
- computer room, IDC UPS.
- New energy generation (solar, wind, PV/wind
- hybrid) access to energy storage system.

- Smart grid, micro-grid system.
- Other energy Storage System.
- Mobile container storage system.
- Load tracking energy storage system.
- Peak load shifting energy storage system.

## Technical Data

MODEL	GE51460FS
Batteries materials	Lithium iron phosphate
Rate voltage	51.2V
Rate capacity	460Ah
Dimensions L*W*H(mm)	385*710*1030
Package Dimension L*W*H(mm)	770*485*1260
Net Weight(kg)	213
Gross Weight(kg)	245.3
Color	Optional
Parallel support	Parallel terminals are supported
Output port mode	Terminal
Charging way	CC/CV
Charging current	0.2C ( standard )
Maximum charging current	Max 0.5C @ 25°C
Charge cut-off voltage	58.4V
Discharge way	CC/CP/VP
Discharge current	1C
Maximum discharge current	Max 1C @ 25°C
Discharge cut-off voltage	44.8V
Communication interface	RS485/RS232/CAN
Charging operating temperature	Charging:0~+50°C
Discharge operating temperature	Discharge:-20~+55°C
The quality assurance period	60 months
Cycle Life	85% DOD ≥ 8000 Time

Product specifications are subject to change without prior notice.

25